

IN THE CLAIMS

Please amend the claims to read as follows:

LISTING OF CLAIMS

1. (Cancelled)

2. (Previously Presented) The emitter as claimed in claim 11, wherein at least one of said first and second mirrors is linked directly by opposed faces to two of said lengths of said optical fiber.

3. (Previously Presented) The emitter as claimed in claim 11, wherein at least one of said first and second mirrors is linked, via an associated optical coupler, to two of said lengths of said optical fiber.

4. (Previously Presented) The emitter as claimed in claim 3, wherein said optical coupler comprises two lenses optically linking said two of said lengths of the optical fiber, the mirror associated with said optical coupler being placed between said two lenses.

5. (Previously Presented) The emitter as claimed in claim 3, wherein said optical coupler comprises at least one graded-index lens.

6. (Previously Presented) The emitter as claimed in claim 11, further comprising an optical element that prevents an electromagnetic pulse generated by said generator from returning toward said generator.

7. (Previously Presented) The emitter as claimed in claim 11, wherein said generator is operable to generate at least two electromagnetic pulses, of different wavelengths.

8. (Currently Amended) A test system for determining the losses of a fiber-optic component, said system comprising:

an optical source operable to emit at least one electromagnetic pulse;

a photoreceiver operable to measure characteristics of an said electromagnetic pulse emitted by said optical source and transmitted by a said fiber-optic component; and

a data acquisition, storage and processing device which receives the measurements generated by said photoreceiver for said fiber-optic component to be tested and for a reference

fiber-optic component and which determines, on the basis of these measurements, the losses of said fiber-optic component to be tested, wherein:

said optical source comprises an emitter including:

a generator that generates at least one electromagnetic pulse;

at least one optical fiber that transmits an said electromagnetic pulse generated by said generator for the purpose of emitting said electromagnetic pulse; and

an optical system including an optical cavity:

which is disposed in a path of said electromagnetic pulse transmitted by said optical fiber; and

which has an input provided with a first partially reflecting mirror and an output provided with a second partially reflecting mirror, wherein:

said first partially reflecting mirror is placed between a first fiber length and a second fiber length of the optical fiber, said first fiber length being linked to the generator,

said second partially reflecting mirror is placed between the second fiber length and a third fiber length of

the optical fiber, said second fiber length being used to link said first and second mirrors together, and

the length of said second fiber length and the transmission and reflection ratio of said first and second mirrors are adjusted such that, there is created at the output of said optical cavity, from a single said electromagnetic pulse incident on said optical cavity, a train of emitted electromagnetic pulses which have variable geometric characteristics emission solid angles and variable emission areas and are associated with said incident electromagnetic pulse.

9. (Previously Presented) The test system as claimed in claim 8, wherein the optical fiber of the emitter for emitting electromagnetic pulses has at least two characteristics, the core diameter and the numerical aperture, which are predetermined and in that at least one of said characteristics of said optical fiber is identical to that of the fiber-optic component to be tested.

10. (Currently Amended) A method of determining the value of at least one characteristic parameter of a fiber-optic component using an emitter that includes a generator that

generates at least one electromagnetic pulse, at least one optical fiber that transmits an said electromagnetic pulse generated by said generator for the purpose of emitting said electromagnetic pulse, and an optical system including an optical cavity which is disposed in a path of said electromagnetic pulse transmitted by said optical fiber and which has an input provided with a first partially reflecting mirror and an output provided with a second partially reflecting mirror, wherein said first partially reflecting mirror is placed between a first fiber length and a second fiber length of the optical fiber, said first fiber length being linked to the generator, said second partially reflecting mirror is placed between the second fiber length and a third fiber length of the optical fiber, said second fiber length being used to link said first and second mirrors together, and the length of said second fiber length and the transmission and reflection ratio of said first and second mirrors are adjusted such that, there is created at the output of said optical cavity, from a single said electromagnetic pulse incident on said optical cavity, a train of emitted electromagnetic pulses which have ~~variable geometric characteristics~~ emission solid angles and variable emission areas and are associated with said incident electromagnetic pulse, said method comprising:

- a) emitting at least one electromagnetic pulse into said fiber-optic component;
- b) carrying out measurements relating to said at least one electromagnetic pulse transmitted by said fiber-optic component; and
- c) determining said characteristic parameter at least from said measurements,

wherein, in step a), an electromagnetic pulse train is generated by means of said emitter, at least some of the electromagnetic pulses of which have different values for at least one optical characteristic, and in step c), the value of said characteristic parameter is determined for each of said different electromagnetic pulses of said pulse train.

11. (Currently Amended) An emitter for emitting electromagnetic pulses, comprising:

a generator that generates at least one electromagnetic pulse;

at least one optical fiber that transmits an said electromagnetic pulse generated by said generator for the purpose of emitting said electromagnetic pulse; and

an optical system including an optical cavity:

which is disposed in a path of said electromagnetic pulse transmitted by said optical fiber; and

which has an input provided with a first partially reflecting mirror and an output provided with a second partially reflecting mirror, wherein:

said first partially reflecting mirror is placed between a first fiber length and a second fiber length of the optical fiber, said first fiber length being linked to the generator,

said second partially reflecting mirror is placed between the second fiber length and a third fiber length of the optical fiber, said second fiber length being used to link said first and second mirrors together, and

the length of said second fiber length and the transmission and reflection ratio of said first and second mirrors are adjusted such that, there is created at the output of said optical cavity, from a single said electromagnetic pulse incident on said optical cavity, a train of emitted electromagnetic pulses which have variable geometric characteristics emission solid angles and variable emission areas and are associated with said incident electromagnetic pulse.